Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-3425

# Body Style:

Flush flange mounting

## **Overall Length:**

1.250 inches

# **Bushing Diameter:**

1.125 inches

### **Overall Diameter:**

2.000 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant

### **Unthreaded Mounting Hole Diameter:**

#### 0.120 inches

### Distance From Mounting Shoulder To Rear Face:

0.750 inches

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

3 single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

30.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

#### Shell Type:

Solid

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Silver single mating end single contact grouping

### **Insert Material:**

Plastic single mating end

#### Shell Material:

Zinc alloy

## Shell Surface Treatment:

Chromate

### **Included Contact Quantity:**

3 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping



Precious Material And Location:

Contact surfaces silver

**Precious Material And Weight:** 

0.003 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0