## NSN 5935-00-259-3956

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-3956

Body Style:
Straight shape
Overall Length:
4.375 inches
Overall Height:
0.328 inches
Overall Width:
1.562 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
3.875 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
4200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
5900.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:

included Contact Type

Round socket single mating end single contact grouping

## NSN 5935-00-259-3956

Electrical Receptacle Connector - Page 2 of 2



## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.034 gold grains, troy and 0.034 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0