

View Online at <https://aerobasegroup.com/nsn/5935-00-259-4120>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.540 inches

**Overall Height:**

Between 2.230 inches and 2.270 inches

**Overall Width:**

Between 2.230 inches and 2.270 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and pressure proof

**Unthreaded Mounting Hole Diameter:**

Between 0.207 inches and 0.213 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.745 inches and 1.755 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.745 inches and 1.755 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.875 inches and 0.891 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-17 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

80.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

2.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.020 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0