

View Online at <https://aerobasegroup.com/nsn/5935-00-259-4179>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.703 inches and 0.797 inches

Overall Height:

Between 1.859 inches and 1.891 inches

Overall Width:

Between 1.859 inches and 1.891 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.149 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.498 inches and 1.508 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.498 inches and 1.508 inches

Distance From Mounting Shoulder To Front Face:

Between 0.422 inches and 0.454 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Fk-g5c single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1300.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.375 inches

Thready Qty Per Inch (tpi):

6

Thread Size:

1.812 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0