NSN 5935-00-259-4312

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-4312 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Unable To Decode:** Unable to decode and unable to decode **Overall Length:** 0.750 inches **Bushing Diameter:** 0.375 inches **Overall Width:** 0.687 inches Diameter: 0.468 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Connector Locking Method:** Latching ring Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-259-4312

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Furnished items - grounding lug and nut
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0