NSN 5935-00-259-4699

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-4699

Thread Direction:
Right-hand
Overall Height:
1.500 inches
Body Length:
1.518 inches
Body Width:
1.500 inches
Environmental Protection:
Vibration resistant and watertight
Unthreaded Mounting Hole Diameter:
0.177 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
900.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts:
Contact Maximum Dc Voltage Rating In Volts:
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method:
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size:
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches Insert Material:
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches Insert Material: Rubber single mating end
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches Insert Material: Rubber single mating end Shell Material:
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy
Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell Thread Size: 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment:

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-259-4699

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0