NSN 5935-00-259-5315

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-5315 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.719 inches **Overall Diameter:** 1.312 inches **Distance From Mounting Shoulder To Front Face:** 0.359 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-79 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 40.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 **Thread Size:** 1.625 inches and 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Ceramic single mating end

Terminal Type:

Turret single mating end single contact grouping

NSN 5935-00-259-5315

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
8 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Banana single mating end single contact grouping
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0