Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-6811

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
0.719 inches
Overall Diameter:
1.312 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
6 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi):
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 1.125 inches and 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Ceramic single mating end

Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Anodize **Included Contact Quantity:** 6 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0