NSN 5935-00-259-6949

Plastic melamine single mating end

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-6949 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 2.719 inches **Overall Height:** 1.125 inches **Overall Width:** 1.094 inches **Distance Between Mounting Facility Centers:** Between 2.125 inches and 2.140 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Bayonet pin and detent Thread Length: 0.328 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:**

NSN 5935-00-259-6949

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
18 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.018 gold grains, troy and 0.018 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A039b0