## NSN 5935-00-259-7380

Electrical Receptacle Connector - Page 1 of 2



-00-259-7380

| View Online at https://aerobasegroup.com/nsn/5935- |
|--|
| Thread Direction:                                  |
| Right-hand and right-hand                          |
| Overall Length:                                    |
| 2.062 inches                                       |
| Overall Height:                                    |
| 1.375 inches                                       |
| Overall Width:                                     |
| 1.375 inches                                       |
| Environmental Protection:                          |
| Pressure proof and corrosion resistant             |
| Unthreaded Mounting Hole Diameter:                 |
| 0.120 inches                                       |
| Distance Between Mounting Facility Centers:        |
| 1.062 inches                                       |
| Threaded Device Type:                              |
| Coupling facility and hub                          |
| Mating End Quantity:                               |
| 1  |
| Contact Maximum Current Rating In Amps:            |
| 35.0 single mating end all contact groupings       |
| Contact Maximum Ac Voltage Rating In Volts:        |
| 500.0 single mating end all contact groupings      |
| Contact Maximum Dc Voltage Rating In Volts:        |
| 700.0 single mating end all contact groupings      |
| Connector Locking Method:                          |
| Externally threaded shell                          |
| Thread Size:                                       |
| 1.125 inches and 1.000 inches                      |
| Insert Material:                                   |
| Plastic single mating end                          |
| Shell Material:                                    |
| Aluminum alloy                                     |
| Included Contact Quantity:                         |
| 5 single mating end all contact groupings          |
| Included Contact Type:                             |
| Round pin single mating end all contact groupings  |
| Special Features:                                  |
| 4 mtg holes; polarized                             |
| Thread Series Designator:                          |
| Unef and unef                                      |
| Shelf Life:  |

N/a

## NSN 5935-00-259-7380

Electrical Receptacle Connector - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A039b0