## NSN 5935-00-259-9650

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-9650

Overall Height: 0.938 inches Overall Width: 0.438 inches Body Length: 1.000 inches Body Angle In Deg: 90.0 Cable Entrance Diameter: 0.312 inches Mating End Quantity: 1 Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Overall Width:  0.438 inches  Body Length:  1.000 inches  Body Angle In Deg:  90.0  Cable Entrance Diameter:  0.312 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  3 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
0.438 inches  Body Length: 1.000 inches  Body Angle In Deg: 90.0  Cable Entrance Diameter: 0.312 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Body Length:  1.000 inches  Body Angle In Deg:  90.0  Cable Entrance Diameter:  0.312 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  3 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
1.000 inches  Body Angle In Deg: 90.0  Cable Entrance Diameter: 0.312 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Body Angle In Deg: 90.0  Cable Entrance Diameter: 0.312 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Cable Entrance Diameter:  0.312 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  3 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Cable Entrance Diameter:  0.312 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  3 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Mating End Quantity:  1 Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Mating End Quantity:  1 Contact Position Arrangement Style: 3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Position Arrangement Style:  3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Position Arrangement Style:  3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
730.0 single mating end single contact grouping  Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Hood, side opening  Connector Cable Strain Relief Method: Cable clamp  Terminal Location: Back single mating end single contact grouping  Contact Material: Copper alloy single mating end single contact grouping  Contact Surface Treatment: Cadmium single mating end single contact grouping  Insert Material: Plastic polyester single mating end  Terminal Type:
Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic polyester single mating end  Terminal Type:
Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Insert Material: Plastic polyester single mating end Terminal Type:
Plastic polyester single mating end  Terminal Type:
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Paint

3 single mating end single contact grouping

## NSN 5935-00-259-9650

Electrical Plug Connector - Page 2 of 2



Included Contact Type
-----------------------

Flat socket single mating end single contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0