

View Online at https://aerobasegroup.com/nsn/5935-00-260-3289

2a         Thread Direction:         Right-hand         Body Style:         Straight shape, rectangular         Overall Length:         5.097 inches         Overall Height:         1.350 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Detecter To Center Distance Between Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contect Position Arrangement Style:         104 single mating end         Polarization Method:         Polarization Method:         Polarization Method:         Screw         Thread Size:         0.250 inches         Special Features:         Polarization bov         Thread Size:         0.250 inches         Special Features:         Polarized in posit	Thread Class:
Tread Direction:         Right-hand         Body Style:         Straight shape, rectangular         Overall Length:         5.097 inches         Overall Height:         1.350 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Ostarce Between Center lines Of Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Widthth         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Context Position Arrangement Style:         104 single mating end         Polarization boss         Connector Locking Method:         Straw         Thread Size:         0.250 inches         Finerad Size:         0.261 inches         Polarization boss         Connector Locking Method:         2.500 inches         Stread         Intread Size:         0.250 inches	
Right-hand         Body Style:         Straight shape, rectangular         Overall Length:         5.097 inches         Overall Meight:         1.350 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         0.419 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Height:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         104 single mating end         Polarization Method:         Polarization boss         Connector Locking Method:         Screw         Thread Size:         0.250 inches         Special Features:         Polarized in position bv         Thread Size:         0.250 inches         Special Features:         Polarized in position bv <tr td="">         Thread Size:</tr>	
Body Style:Straight shape, rectangularOverall Length:3.097 inchesOverall Height:1.350 inchesOverall Width:2.875 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUthreaded Mounting Hole Diameter:0.149 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.812 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width2.500 inchesThreaded Device Type:Coupling facilityMating End Quantiy:1Context Position Arrangement Style:104 single mating endPolarization Method:Polarization bessConcert Locking Method:2.500 inchesPireaded Size:0.250 inchesPireade Jup Ench (tpi):28Pireade Size:0.250 inchesSpecial Features:Piolarized in position bvThread Size:0.250 inchesSpecial Features:Piolarized in position bvThread Size:0.250 inchesSpecial Features:Piolarized in position bvThread Size:104 siries Designator:UnfShell Life:NaNaNaNaNaNaNaNaNaNaNaNaNaNaNa	
Straight shape, rectangular         Overall Length:         5.097 inches         Overall Height:         1.350 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Widthte:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         104 single mating end         Polarization Method:         Polarization boss         Connector Locking Method:         Screw         Thready Gty Per Inch (tpi):         28         Piolarized in position bv         Thread Size:         0.250 inches         Special Features:         Polarized in position bv         Thread Size:         Oplarized in position bv         Thread Series Designator:         Unf	-
Overall Length:5.097 inchesOverall Height:1.350 inchesOverall Width:2.875 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUntreaded Mounting Hole Diameter:0.149 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.812 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Widththe2.500 inchesThreaded Device Type:Coupling facilityMating End Quantity:11Polarization Method:Polarization bossConnector Locking Method:ScrewThready Cty Per Inch (tpi):28Picati Size:0.250 inchesSpecial Features:Polarized in position bvThread Size:Distaries Designator:UnfShell Life:N/a	
S.097 inches         Overall Height:         1.350 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Widtht:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contect Position Arrangement Style:         104 single mating end         Polarization Method:         Polarization boss         Cornector Locking Method:         Screw         Thread Size:         0.250 inches         Pinead Size:         0.250 inches         Pinead Size:         0.250 inches         Pinead Size:         0.250 inches         Pinead Size:         Polarized in position bv         Thread Series Designator:         Unf         Shelf Life:         V/a <th></th>	
Overall Height:         1.360 inches         Overall Width:         2.875 inches         Environmental Protection:         Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contect Position Arrangement Style:         104 single mating end         Polarization bethod:         Polarization boss         Connector Locking Method:         Screw         Thread Size:         0.250 inches         Special Features:         Polarized in position bv         Thread Sries Designator:         Unif         Mating End Endures:	-
1.350 inchesOverall Width:2.875 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.149 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.812 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:2.500 inchesThreaded Device Type:Coupling facilityMating End Quantity:11Polarization Method:Polarization bossConnector Locking Method:2srewThread Size:0.250 inchesSpecial Features:Polarizet in position bvThread Size:0.250 inchesSpecial Features:Polarizet in position bvThread Sires:Polarizet in position bvThread Sires:Polarizet in position bvThread Sires Designator:UnfNaNa	
Overall Width:2.875 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.149 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.812 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width2.500 inchesThreaded Device Type:Coupling facilityMating End Quantity:11Polarization Method:Polarization bossConnector Locking Method:28Thread Size:0.250 inchesSpecial Features:Polarized in position bvThread Size:0.250 inchesSpecial Features:Polarized in position bvThread Size:0.125 inchesSpecial Features:Polarized in position bvThread Sires Designator:UnfMainShelf Life:N/a	
2.875 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Coupling facility Mating End Quantity: 1 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization boss Connector Locking Method: Sorew Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Moisture resistant and salt water resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.149 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         0.812 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         2.500 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         104 single mating end         Polarization Method:         Polarization boss         Connector Locking Method:         Screw         Thready Qty Per Inch (tpi):         28         Polarized in position bv         Thread Size:         0.250 inches         Special Features:         Polarized in position bv         Thread Siries Designator:         Unf         Shelf Life:         N/a	
Unthreaded Mounting Hole Diameter: 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Sheff Life: N/a	
0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Sheff Life: N/a	
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thread y Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	-
0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
2.500 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Threaded Device Type:
Mating End Quantity:1Contact Position Arrangement Style:104 single mating endPolarization Method:Polarization bossConnector Locking Method:ScrewThready Qty Per Inch (tpi):28Thread Size:0.250 inchesSpecial Features:Polarized in position bvThread Series Designator:UnfShelf Life:N/a	
1 Contact Position Arrangement Style: 104 single mating end Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
104 single mating end Polarization Method: Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	
Polarization Method:Polarization bossConnector Locking Method:ScrewThready Qty Per Inch (tpi):28Thread Size:0.250 inchesSpecial Features:Polarized in position bvThread Series Designator:UnfShelf Life:N/a	Contact Position Arrangement Style:
Polarization boss Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	104 single mating end
Connector Locking Method: Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Polarization Method:
Screw Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Polarization boss
Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Connector Locking Method:
28 Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Screw
Thread Size: 0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	Thready Qty Per Inch (tpi):
0.250 inches Special Features: Polarized in position bv Thread Series Designator: Unf Shelf Life: N/a	28
Special Features:         Polarized in position bv         Thread Series Designator:         Unf         Shelf Life:         N/a	Thread Size:
Polarized in position bv <b>Thread Series Designator:</b> Unf <b>Shelf Life:</b> N/a	0.250 inches
Thread Series Designator: Unf Shelf Life: N/a	Special Features:
Unf Shelf Life: N/a	Polarized in position by
Shelf Life: N/a	Thread Series Designator:
N/a	Unf
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--



Demilitarization:

Yes - demil/mli

Fiig:

A039b0