NSN 5935-00-261-6781

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-261-6781 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.375 inches **Overall Diameter:** 1.266 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-10 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.367 inches **Thread Size:** 0.938 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-00-261-6781Electrical Plug Connector - Page 2 of 2



Aluminum alloy 6061 Shell Surface Treatment: Anodize Shell Material Specification: Qq-a-367, t6 federal specification single material response Included Contact Quantity:	
Anodize Shell Material Specification: Qq-a-367, t6 federal specification single material response	
Shell Material Specification: Qq-a-367, t6 federal specification single material response	
Qq-a-367, t6 federal specification single material response	
Included Contact Quantity:	
morados contact stantity.	
10 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.010 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-26500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cer	ain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef	
Specification Data:	
81349-mil-c-26500 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	