Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-261-6879

### **Body Style:**

Straight shape, external coupling

### **Overall Length:**

0.697 inches

### **Overall Height:**

1.234 inches

### **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.970 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

### 0.970 inches

### **Distance From Mounting Shoulder To Front Face:**

0.442 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16-8 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

342.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy



#### Shell Surface Treatment:

Cadmium and chromate

#### **Included Contact Quantity:**

8 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.008 gold grains, troy and 0.008 silver grains, troy

#### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-38999 government specification

# Shelf Life:

N/a

Unit Of Measure:

# --

Demilitarization:

No

Fiig:

A039b0