

View Online at <https://aerobasegroup.com/nsn/5935-00-270-1192>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Black

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.922 inches and 1.000 inches

Mounting Bushing Length:

Between 0.375 inches and 0.438 inches

Overall Diameter:

Between 0.281 inches and 0.343 inches

Bushing Accommodation Hole Shape:

Round

Maximum Voltage Rating In Volts:

2000.0 ac

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.079 inches and 0.081 inches single finger

Finger Accommodation Length:

0.500 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L01336

Material:

Copper alloy terminal

Material:

Plastic polyamide insulator

Precious Material And Location:

Contact spring surface gold

Precious Material:

Gold

Surface Treatment:

Gold spring

Surface Treatment:

Gold spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03400