

View Online at <https://aerobasegroup.com/nsn/5935-00-270-3526>

Body Style:

Straight shape

Overall Length:

Between 3.840 inches and 3.860 inches

Overall Height:

0.662 inches

Overall Width:

0.385 inches

Environmental Protection:

Corrosion resistant and salt water resistant and shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.119 inches and 0.123 inches

Distance Between Mounting Facility Centers:

3.250 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Terminal Location:

Back corner single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613 1/2 h federal specification single material response single mating end single contact grouping or qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 sgd-f military specification single material response single mating end

Included Contact Quantity:

74 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.074 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.