

View Online at <https://aerobasegroup.com/nsn/5935-00-270-3639>

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 1.860 inches and 1.890 inches

Overall Height:

0.677 inches

Overall Width:

Between 0.325 inches and 0.335 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

Between 1.570 inches and 1.580 inches

Board Accommodated Length:

1.100 inches single board and 1.115 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 11 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder stud single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, type gd1-30 military specification single material response single mating end or mil-m-14, type sdg military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.