Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-271-1772

## **Body Style:**

Straight shape, external coupling w/backshell

## **Overall Length:**

0.692 inches

## **Overall Height:**

1.234 inches

## **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.970 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.970 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.317 inches and 0.322 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16-26 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

342.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy



Shell Surface Treatment:

Cadmium and nickel

**Included Contact Quantity:** 

26 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surface gold and contact surface silver

### **Precious Material And Weight:**

0.026 gold grains, troy and 0.026 silver grains, troy

### **Precious Material:**

Gold and silver

## **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0