

View Online at <https://aerobasegroup.com/nsn/5935-00-274-7348>

Thread Class:

2a and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.187 inches

Overall Diameter:

1.469 inches

Environmental Protection:

Vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20-20 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

35.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

150.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

200.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded coupling nut

Thread Length:

0.625 inches and 0.625 inches

Thread Size:

1.125 inches and 1.188 inches

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Thread Series Designator:

Unef and unef

Specification Or Standard:

A class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0