

View Online at <https://aerobasegroup.com/nsn/5935-00-280-2388>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

7.750 inches

**Overall Diameter:**

3.062 inches

**Environmental Protection:**

Explosion proof and watertight

**Cable Entrance Diameter:**

Between 0.375 inches and 0.875 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

B4s single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

60.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

230.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Shell twistlock

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic melamine single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0