NSN 5935-00-283-2660

Connector Adapter - Page 1 of 2



Connector Adapter - Lage 1 of 2
View Online at https://aerobasegroup.com/nsn/5935-00-283-2660
Body Style:
Straight shape, external/internal coupling
Overall Length:
3.500 inches
Overall Diameter:
2.000 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

9.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and spring friction

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic phenolic all mating ends

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Shell Material Specification:

Qq-a-.225/8, t6 federal specification single material response

Insert Material Specification:

Mil-m-14, type mfh military specification single material response all mating ends

Included Contact Quantity:

61 2nd mating end all contact groupings

NSN 5935-00-283-2660

Connector Adapter - Page 2 of 2



Included Contact Type:	
Round socket 2nd mating end all contact groupings	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Mil-m-14 spec.

A039b0