NSN 5935-00-283-2906

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-283-2906 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.093 inches **Overall Height:** 2.125 inches **Overall Width:** 2.125 inches **Unthreaded Mounting Hole Diameter:** 0.169 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.680 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.680 inches **Distance From Mounting Shoulder To Front Face:** 0.437 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Fk-19 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 15.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2050.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring

6

Thready Qty Per Inch (tpi):

NSN 5935-00-283-2906

Electrical Receptacle Connector - Page 2 of 2



Thread Size:	
1.938 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic phenolic single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Included Contact Quantity:	
19 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.019 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Un	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Filig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	