NSN 5935-00-283-2915

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-283-2915 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-4 single mating end **Contact Removability:** Removable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 73.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-283-2915

Electrical Receptacle Connector - Page 2 of 2



inread Size:
1.375 inches
Terminal Location:
Back single mating end all contact groupings
Геrminal Туре:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
ncluded Contact Quantity:
2 single mating end 2nd contact grouping
ncluded Contact Type:
Round pin single mating end all contact groupings
Γhread Series Designator:
Jn
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0