Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-283-3363

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.312 inches
Overall Height:
1.281 inches
Overall Width:
1.281 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Hub
Mating End Quantity:
1
Contact Position Arrangement Style:
16-10 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell



Thread Length: 0.625 inches **Thread Size:** 1.000 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Silver all mating ends all contact groupings **Terminal Type:** Solder well all mating ends all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 3 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round socket all mating ends all contact groupings **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0