NSN 5935-00-283-3733

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-283-3733 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Unable To Decode:** Unable to decode and unable to decode **Overall Length:** 0.531 inches **Bushing Diameter:** 0.375 inches **Overall Width:** 0.625 inches Diameter: 0.500 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: **Connector Locking Method:** Lock ring **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-283-3733

Electrical Receptacle Connector - Page 2 of 2



_					-		
r -	n	+-	rt.	NЛ	210	ria	
·	OI.	ιca	·ι	IVI	alc	ı ıa	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 1 or 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

4 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - nut and grounding lug

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.