## NSN 5935-00-283-7113

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-283-7113

Overall Length:  1.562 inches  Overall Height:  1.062 inches  Overall Width:  0.688 inches  Body Length:  1.000 inches  Cable Entrance Diameter:  0.438 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  6 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:  Steel				
Overall Height:  1.062 inches Overall Width:  0.688 inches Body Length:  1.000 inches Cable Entrance Diameter:  0.438 inches Mating End Quantity:  1 Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Overall Length:			
1.062 inches Overall Width: 0.688 inches Body Length: 1.000 inches Cable Entrance Diameter: 0.438 inches Mating End Quantity: 1 Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	1.562 inches			
Overall Width:  0.688 inches  Body Length:  1.000 inches  Cable Entrance Diameter:  0.438 inches  Mating End Quantity:  1  Contact Position Arrangement Style: 6 single mating end  Contact Removability: Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping  Polarization Method: Contact  Shell Type: Hood, side opening  Connector Cable Strain Relief Method: Cable clamp  Terminal Location: Back single mating end single contact grouping  Contact Material: Copper alloy single mating end single contact grouping  Contact Surface Treatment: Cadmium single mating end single contact grouping  Insert Material: Plastic phenolic single mating end  Terminal Type: Tab, solder lug single mating end single contact grouping  Shell Material:	Overall Height:			
0.688 inches  Body Length: 1.000 inches  Cable Entrance Diameter: 0.438 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	1.062 inches			
Body Length:  1.000 inches  Cable Entrance Diameter:  0.438 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  6 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Overall Width:			
Cable Entrance Diameter:  0.438 inches  Mating End Quantity:  1  Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	0.688 inches			
Cable Entrance Diameter:  0.438 inches  Mating End Quantity:  1  Contact Position Arrangement Style: 6 single mating end  Contact Removability: Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping  Polarization Method: Contact  Shell Type: Hood, side opening  Connector Cable Strain Relief Method: Cable clamp  Terminal Location: Back single mating end single contact grouping  Contact Material: Copper alloy single mating end single contact grouping  Contact Surface Treatment: Cadmium single mating end single contact grouping  Insert Material: Plastic phenolic single mating end  Terminal Type: Tab, solder lug single mating end single contact grouping  Shell Material:	Body Length:			
Mating End Quantity:  1 Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	1.000 inches			
Mating End Quantity:  1 Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Cable Entrance Diameter:			
Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	0.438 inches			
Contact Position Arrangement Style: 6 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Mating End Quantity:			
Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	1			
Contact Removability:  Nonremovable single mating end single contact grouping  Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Contact Position Arrangement Style:			
Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	6 single mating end			
Contact Maximum Current Rating In Amps:  10.0 single mating end single contact grouping  Contact Maximum Ac Voltage Rating In Volts:  730.0 single mating end single contact grouping  Polarization Method:  Contact  Shell Type:  Hood, side opening  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Contact Removability:			
Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Nonremovable single mating end single contact grouping			
Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Contact Maximum Current Rating In Amps:			
Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	10.0 single mating end single contact grouping			
Polarization Method: Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Contact Maximum Ac Voltage Rating In Volts:			
Contact Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	730.0 single mating end single contact grouping			
Shell Type: Hood, side opening Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Polarization Method:			
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Contact			
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Shell Type:			
Cable clamp  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Hood, side opening			
Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Connector Cable Strain Relief Method:			
Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Cable clamp			
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Terminal Location:			
Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Back single mating end single contact grouping			
Contact Surface Treatment:  Cadmium single mating end single contact grouping  Insert Material:  Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Contact Material:			
Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Copper alloy single mating end single contact grouping			
Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:	Contact Surface Treatment:			
Plastic phenolic single mating end  Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Cadmium single mating end single contact grouping			
Terminal Type:  Tab, solder lug single mating end single contact grouping  Shell Material:	Insert Material:			
Tab, solder lug single mating end single contact grouping  Shell Material:	Plastic phenolic single mating end			
Shell Material:	Terminal Type:			
	Tab, solder lug single mating end single contact grouping			
Steel	Shell Material:			
	Steel			
Shell Surface Treatment:				
Paint				
	Included Contact Quantity:			

6 single mating end single contact grouping

## NSN 5935-00-283-7113

Electrical Plug Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Flat socket single mating end single contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0