

View Online at <https://aerobasegroup.com/nsn/5935-00-283-7134>

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.969 inches and 1.219 inches

Bushing Diameter:

Between 0.435 inches and 0.445 inches

Overall Height:

Between 0.995 inches and 1.005 inches

Overall Width:

Between 0.995 inches and 1.005 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.714 inches and 0.722 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.714 inches and 0.722 inches

Distance From Mounting Shoulder To Front Face:

Between 0.655 inches and 0.685 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

C single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.