

View Online at <https://aerobasegroup.com/nsn/5935-00-283-8299>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.938 inches

Overall Height:

Between 1.969 inches and 2.031 inches

Overall Width:

Between 1.969 inches and 2.031 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.562 inches

Distance From Mounting Shoulder To Front Face:

0.812 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-21 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1, grade b federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

96906-ms3102 government standard

Shelf Life:

N/a

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.