

View Online at <https://aerobasegroup.com/nsn/5935-00-284-3618>

Body Style:

Hood, top opening, w/clamp

Overall Length:

2.250 inches

Overall Height:

2.250 inches

Overall Width:

1.250 inches

Cable Entrance Diameter:

0.625 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Shell

Shell Type:

Hood, top opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Insert Material Specification:

Mil-m-14, ty sdc military specification single material response single mating end

Shell Guide Type And Location Designator:

A pin and d pin and 2 pin and 5 pin

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Color:

Natural

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Fsc Application Data (non-core):

Connectors, electrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.