Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-295-3083

# Thread Direction:

Right-hand and right-hand

## **Overall Length:**

0.979 inches

## **Overall Height:**

1.281 inches

## Overall Width:

1.281 inches

## **Environmental Protection:**

Humidity resistant and salt water resistant and fuel proof and corrosion resistant

# Unthreaded Mounting Hole Diameter:

0.120 inches

# Distance Between Mounting Facility Centers:

0.906 inches

# Threaded Device Type:

# Coupling facility and hub

Mating End Quantity:

1

### Contact Maximum Current Rating In Amps:

22.0 single mating end all contact groupings

### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

### Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

### **Connector Locking Method:**

Externally threaded shell

### Thread Size:

1.000 inches and 0.875 inches

### Insert Material:

Rubber synthetic single mating end

### Shell Material:

Aluminum alloy

### **Included Contact Quantity:**

7 single mating end all contact groupings

### Included Contact Type:

Round pin single mating end all contact groupings

### **Special Features:**

4 mtg holes; polarized; dim. Excl contacts

### **Thread Series Designator:**

Unef and unef

### Shelf Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0