Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-295-5285

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 1.188 inches **Overall Diameter:** 0.469 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Included Contact Quantity:** 1 single mating end single contact grouping

NSN 5935-00-295-5285

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape: Round Included Contact Type: Coaxial pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.005 gold grains, troy Precious Material: Gold Thread Series Designator: Unef Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0