NSN 5935-00-295-5307

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-295-5307 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.844 inches **Overall Height:** 1.125 inches **Overall Width:** 1.234 inches **Distance Between Mounting Facility Centers:** Between 2.276 inches and 2.286 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 4000.0 single mating end single contact grouping **Polarization Method:** Mating end and guide pin/socket Shell Type: Solid **Connector Locking Method:** Detent Thread Length: 0.328 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:**

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-295-5307

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0