Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-295-5401

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.464 inches |
| Overall Height: |
| 0.531 inches |
| Overall Width: |
| 0.784 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.332 inches |
| Distance Between Mounting Facility Centers: |
| 2.113 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 10.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 110.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| |

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right handandjackscrew type-male and location-left hand

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0