## NSN 5935-00-296-8288

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-296-8288 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.312 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-11 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 35.0 Shell Type: Solid **Connector Locking Method:** 

Detent

## NSN 5935-00-296-8288

Electrical Receptacle Connector - Page 2 of 2



| Thread Size:  |
|---|
| 1.500 inches and 1.438 inches   |
| Terminal Location:  |
| Back single mating end all contact groupings  |
| Terminal Type:  |
| Solder well single mating end all contact groupings   |
| Shell Material:   |
| Aluminum alloy  |
| Included Contact Quantity:  |
| 6 single mating end 2nd contact grouping  |
| Included Contact Type:  |
| Round pin single mating end all contact groupings   |
| Test Data Document:   |
| 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Thread Series Designator:   |
| Unef and unef   |
| Specification Data:   |
| 81349-mil-c-5015 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
|   |
|   |