NSN 5935-00-296-8579

Body Style:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-296-8579

Hood, side opening w/clamp
Overall Length:
2.438 inches
Overall Height:
1.844 inches
Overall Width:
1.125 inches
Cable Entrance Diameter:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
730.0 single mating end single contact grouping
Polarization Method:
0
Contact
Shell Type:
Shell Type:
Shell Type: Hood, side opening
Shell Type: Hood, side opening Connector Locking Method:
Shell Type: Hood, side opening Connector Locking Method: Spring friction
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type:
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Solder well single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:

NSN 5935-00-296-8579

Electrical Plug Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

15 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0