Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-296-8791

Body Style:

Hood, top opening, w/clamp

Overall Length:

3.719 inches

Overall Height:

2.344 inches

Overall Width:

1.250 inches

Environmental Protection:

Vibration resistant

Cable Entrance Diameter:

0.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

32 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Shell

Insert Position In Deg:

0.0

Shell Type:

Hood, top opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-296-8791 Electrical Plug Connector - Page 2 of 2



Tab, s	older lug single mating end single contact grouping
	Aaterial:
Coppe	r alloy
Shell S	Surface Treatment:
Nickel	
Insert	Material Specification:
Mil-m-1	14, ty sdg military specification single material response single mating end
Shell C	Guide Type And Location Designator:
A pin a	nd c pin and 3 pin and 6 pin
Includ	ed Contact Quantity:
32 sing	le mating end single contact grouping
Includ	ed Contact Type:
Leaf sp	pring single mating end single contact grouping
Specia	Il Features:
Positio	n 1 polarization
Precio	us Material And Location:
Contac	t surfaces gold
Precio	us Material And Weight:
0.032 g	gold grains, troy
Precio	us Material:
Gold	
Shelf L	life:
N/a	
Unit O	f Measure:
Demili	tarization:
No	
Fiig:	
A039b0	0
Mil-std	l (military Standard):
Mil-g-4	5204 spec.