

View Online at <https://aerobasegroup.com/nsn/5935-00-299-7897>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

Between 2.115 inches and 2.135 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.745 inches and 1.755 inches

Overall Height:

1.420 inches

Overall Width:

Between 0.820 inches and 0.840 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.143 inches and 0.155 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36 single mating end

Polarization Method:

Polarization boss

Connector Locking Method:

Post jacksocket

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Insert Material Specification:

Mil-m-14, ty sgd-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response single mating end

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

1 Inc

Specification Data:

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.