NSN 5935-00-301-5736



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-301-5736

| Thread Class: |
|---|
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 2.500 inches |
| Overall Height: |
| 2.250 inches |
| Overall Width: |
| 2.250 inches |
| Environmental Protection: |
| Moisture proof and salt water resistant and vibration proof |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.750 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.875 inches |
| Threaded Device Type: |
| Coupling facility and mounting hole |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 18 and 32 |
| Thread Size: |
| 2.000 inches and 0.138 inches |
| Terminal Location: |

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-00-301-5736

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|---|
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1, |
| grade b federal specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification all treatment responses |
| Included Contact Quantity: |
| 35 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.035 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unf and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.