NSN 5935-00-301-5736



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-301-5736

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.500 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.750 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 32
Thread Size:
2.000 inches and 0.138 inches
Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-00-301-5736

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1,
grade b federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
35 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.035 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.