

View Online at <https://aerobasegroup.com/nsn/5935-00-303-2010>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Rectangular shape

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches

Overall Height:

0.874 inches

Overall Width:

0.760 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.468 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

12

Polarization Method:

Guide pin/socket and 2 polarization posts

Connector Locking Method:

Friction and latch

Thready Qty Per Inch (tpi):

40 and 40 and 32

Thread Size:

0.112 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Insert Material Specification:

Mil-m-14, sdg-f military specification single material response single mating end or mil-p-19833, gdi-30f military specification single material response single mating end

Special Features:

Replace standard lock nuts and washers w/esna (brand name) nuts and washers, no change in size

Color:

Gray

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.