

View Online at <https://aerobasegroup.com/nsn/5935-00-311-3942>

Thread Class:

2b

Thread Direction:

Right-hand

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

440.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Compression nut

Thread Size:

1.938 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

46b10g, comp. N-c mfr ref single material response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

3 wire-4 pole type

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0