Electrical Receptacle Connector - Page 1 of 2



| Electrical Receptacle Connector - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-00-314-4244 |
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.625 inches |
| Overall Height: |
| 1.047 inches |
| Overall Width: |
| 0.500 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.138 inches |
| Distance Between Mounting Facility Centers: |
| 1.250 inches |
| Threaded Device Type: |
| Mounting hole |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 28-833 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Thread Size: |
| 0.138 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-p-14, type mme military specification single material response single mating end |
| |

NSN 5935-00-314-4244

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 7 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.001 gold grains, troy and 0.001 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-14 spec.