Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1602

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 2.095 inches and 2.105 inches
Overall Height:
Between 0.795 inches and 0.805 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Distance Between Mounting Facility Centers:
Between 1.795 inches and 1.805 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.250 inches
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping or copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single
material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end
single contact grouping and qq-w-321 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-g-14, type sdg-f military specification single material response single mating end

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Test Data Document:

81349-mil-c-55302/16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-55302/16 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-14 spec.