NSN 5935-00-318-1624

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1624 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.825 inches **Overall Diameter:** Between 1.234 inches and 1.266 inches **Environmental Protection:** Hermetic **Distance From Mounting Shoulder To Front Face:** Between 0.665 inches and 0.727 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 12-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass single mating end **Terminal Type:**

Solder well single mating end single contact grouping

NSN 5935-00-318-1624 Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Gold
Included Contact Quantity:
10 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.110 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0