## NSN 5935-00-318-1806

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1806 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape w/screw locks **Overall Length:** Between 0.845 inches and 0.855 inches **Overall Height:** 1.060 inches **Overall Width:** Between 0.245 inches and 0.255 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and moisture resistant and cold resistant and heat resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.125 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end

## NSN 5935-00-318-1806

Electrical Plug Connector - Page 2 of 2



## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:** 

9 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Special Features:** 

Polarizing pin in contact position 3

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.009 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.