NSN 5935-00-318-1834

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1834 **Thread Class:** 2a and 2g **Thread Pitch Diameters:** +1.989/+2.000 inches **Thread Direction:** Left-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Height:** 2.250 inches **Overall Width:** 2.250 inches **Environmental Protection:** Corrosion resistant and humidity resistant and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.203 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.688 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.688 inches **Distance From Mounting Shoulder To Front Face:** 1.000 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:**

0.0

Shell Type:

Solid

NSN 5935-00-318-1834

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.406 inches
Thready Qty Per Inch (tpi):
18 and 8
Thread Size:
1.613 inches and 2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Silicon single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.095 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Npt and acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0