## NSN 5935-00-318-1836

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1836

View Online at https://aerobasegroup.com/nsn/5935-00-318-1836
Thread Class:
2g
Thread Pitch Diameters:
+2.000/+2.011 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
5.719 inches
Overall Diameter:
2.469 inches
Environmental Protection:
Corrosion resistant and humidity resistant and moisture resistant and vibration resistant
Cable Entrance Diameter:
Between 0.750 inches and 0.875 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
Contact Maximum Ac Voltage Nating in Volts.
500.0 single mating end single contact grouping
500.0 single mating end single contact grouping
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  0.0
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  0.0  Shell Type:
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  0.0  Shell Type:  Solid
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts:  700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  0.0  Shell Type:  Solid  Connector Locking Method:
500.0 single mating end single contact grouping  Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  0.0  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling nut

8

Thready Qty Per Inch (tpi):

## **NSN 5935-00-318-1836**Electrical Plug Connector - Page 2 of 2



Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Silicon single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.095 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0