## NSN 5935-00-318-1858

**Body Style:** 

Straight shape, rectangular

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-1858

**Overall Length:** 0.803 inches **Overall Height:** 0.780 inches **Overall Width:** 1.940 inches **Unthreaded Mounting Hole Diameter:** 0.136 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.468 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.420 inches **Mating End Quantity: Contact Position Arrangement Style:** 38 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1850.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

## NSN 5935-00-318-1858

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 38 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.038 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):