

View Online at <https://aerobasegroup.com/nsn/5935-00-318-2787>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

4.650 inches

**Overall Height:**

0.685 inches

**Overall Width:**

Between 0.542 inches and 0.552 inches

**Distance Between Mounting Facility Centers:**

4.288 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1300.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end and glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Guide Design And Location:**

Hexagon shape male post left-hand at 7 oclock and hexagon shape female post right-hand at 7 oclock

**Included Contact Quantity:**

76 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.076 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.