NSN 5935-00-318-6370

Thread Class: 2a and 2b

Thread Direction:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-318-6370

| Right-hand and right-hand |
|---|
| Body Style: |
| Right angle, card |
| Overall Length: |
| 4.281 inches |
| Overall Width: |
| 0.375 inches |
| Body Height: |
| 0.375 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Length: |
| 0.315 inches |
| Thread Size: |
| 0.100 inches and 0.125 inches |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| 5 5 |
| Terminal Type: |

Included Contact Quantity:

37 single mating end single contact grouping

NSN 5935-00-318-6370

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Type: |
|---|
| Round pin single mating end single contact grouping |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A039b0